

## 1. Product Information

Supplier: JIANGSU CHANGJING ELECTRONICS TECHNOLOGY CO.,LTD.

<b>Part Number:</b>	CJAC5R0SN03A
<b>Package Type:</b>	PDFNWB5x6-8L
<b>Part Description:</b>	SMD/MOSFET
<b>Report Date:</b>	October-2025

## 2. Reliability Test Results: PASS

Test Item	Test Condition	Duration	Fail Quantity / S.S
Pre-and post-stress Electrical test	Ta=25°C	—	All parts
<b>PC</b> Precondition(For SMD Package Only)	JESD22-A113F/J-STD-020 1.Bake:125°C 2.Soak: 85°C85%RH,168Hours MSL1 or 30°C60%RH,192Hours MSL3 3.Reflow 3Cycles Max 260°C 4.all samples E-Test	>168Hours or >192Hours	0 / 308*3
<b>TCT</b> Temperature Cycling Test	JESD22 -A104 -55°C/15min 150°C/15min	1000Cycles	0 / 77*3
<b>AC</b> Autoclave	JESD22-A102 121°C, 100%RH	96Hours	0 / 77*3
<b>UHAST</b> Unbiased Highly Accelerated Stress Test	JESD22-A118 130°C, 85%RH	96Hours	—
<b>THT</b> High Humidity &Temp. Test	JESD22-A101 85°C 85%RH	1000Hours	0 / 77*3
<b>HTST</b> High Temperature Storage Test	JESD22 -A103 T=Tstg max	1000Hours	0 / 77*3
<b>H3TRB</b> High Humidity &Temp. Bias Test	JESD22-A101 85°C 85%RH VDS*80% VDS≤100V Max	1000Hours	—
<b>HAST</b> Highly Accelerated Stress Test	JESD22-A110 130°C 85%RH VDS*80% VDS≤42V Max	96Hours	0 / 77*3

**HTRB**  
High Temperature Revers Bias Test

### Notes:

1. Either H3TRB or HAST for reliability test.
2. Either AC or UHAST for reliability test.
3. Detailed MSL of the product refers to the MSL Report.

Remark: JSCJ Laboratory reserves the right of final interpretation of this report